

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ZINC-THANE 2805 ZINC-RICH PRIMER
PRODUCT CODE: ZINCTHANE2805P

HMIS CODES: H 3 F 1 R 1 P K

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: INDMAR COATINGS CORP.
ADDRESS: P.O. BOX 456, WAKEFIELD, VA 23888
EMERGENCY PHONE: 1-757-899-3807
DATE REVISED: 2/05

INFORMATION PHONE: 1-757-899-3807
NAME OF PREPARER: M. WHITED

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

Table with 7 columns: HAZARDOUS COMPONENTS, CAS NUMBER, OCCUPATIONAL EXPOSURE LIMITS (OSHA PEL, ACGIH TLV, OTHER), VAPOR PRESSURE (mm Hg @ TEMP), and WEIGHT PERCENT. Rows include SUPER HIGH FLASH NAPHTHA, AROMATIC POLYISOCYANATE PREPOLYMER, and ZINC DUST.

\*Indicates toxic chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.

\*, \*\*, #, ##, #\*, #@, @@, BEHIND THE TLV & PEL VALUES INDICATE SPECIAL HEALTH AND FIRE HAZARD NOTATIONS TO BE FOUND IN THE BODY OF THE MSDS. READ ALL SECTIONS CAREFULLY AND CHECK FOR NOTATIONS.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 313 to 1665 Deg F
VAPOR DENSITY: HEAVIER THAN AIR
COATING V.O.C.: 2.80 LB/GAL (336 G/L)
MATERIAL V.O.C.: 2.80 LB/GAL (336 G/L)
SOLUBILITY IN WATER: NOT SOLUBLE IN WATER
APPEARANCE AND ODOR: COLORED VISCOUS LIQUID WITH AROMATIC SOLVENT ODOR

SPECIFIC GRAVITY (H2O=1): 3.1
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 114 Deg F
FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 0.5% UPPER: 6.0%
METHOD USED: TCC

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR BE MOVED BY VENTILATION AND IGNITED BY HEAT, PILOT LIGHTS, OTHER FLAMES AND IGNITION SOURCES AT LOCATIONS DISTANT FROM MATERIAL HANDLING PORT.

=====  
SECTION V - REACTIVITY DATA  
=====

**STABILITY:** STABLE

**CONDITIONS TO AVOID**

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUMS(EVEN EMPTY) BECAUSE PRODUCT(EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

**HAZARDOUS DECOMPOSITION OR BYPRODUCTS**

MAY FORM TOXIC MATERIALS; CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

**HAZARDOUS POLYMERIZATION:** WILL NOT OCCUR

=====  
SECTION VI - HEALTH HAZARD DATA  
=====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION, DIZZINESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONCIOUSNESS, AND EVEN ASPHYXIATION.\*\*AS NUISANCE DUSTS. #AS RESPIRABLE NUISANCE DUSTS.

**SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

PROLONGED OR REPEATED CONTACT WITH PRODUCT CAN CAUSE MODERATE SKIN IRRITATION, DEFATTING, DERMATITIS. EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION.

**SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

@SKIN ABSORPTION MAY POTENTIALLY CONTRIBUTE TO OVERALL EXPOSURE TO THIS MATERIAL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT TLV IS NOT INVALIDATED.

**INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITTING, AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL.

**HEALTH HAZARDS (ACUTE AND CHRONIC)**

ACUTE: IRRITATION OF SKIN, EYES, MUCOUS MEMBRANES. DRYING, DEFATTING OF SKIN. AVOID INGESTION AND BREATHING OF VAPORS.

CHRONIC: EYE, LIVER, KIDNEY, AND CENTRAL NERVOUS SYSTEM DAMAGE MAY OCCUR.

**CARCINOGENICITY:** NTP? NO      **IARC MONOGRAPHS?** NO      **OSHA REGULATED?** NO

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE****EMERGENCY AND FIRST AID PROCEDURES**

SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CLOTHING BEFORE REUSE.

EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITTING. KEEP PERSON WARM, QUIET, AND GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO LUNGS DUE TO VOMITTING CAN CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL.

BREATHING: REMOVE PERSON TO FRESH AIR. GIVE OXYGEN IF BREATHING DIFFICULT; GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPS. KEEP PERSON WARM AND GET MEDICAL ATTENTION.

=====  
**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**  
=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

SMALL: ABSORB, PREFERRABLY WITH FLOOR ABSORBENT. TRANSFER TO HOOD.

LARGE: ELIMINATE ALL IGNITION SOURCES. WEAR PROTECTIVE CLOTHING. STOP SPILL, DIKE AREA, PUMP TO SALVAGE TANK. PREVENT RUN-OFF TO SEWERS, STREAMS. NOTIFY AUTHORITIES.

**WASTE DISPOSAL METHOD**

SMALL SPILL: ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD. ALLOW SUFFICIENT TIME FOR VAPORS TO COMPLETELY CLEAR HOOD DUCT WORK. DISPOSE OF REMAINING MATERIAL IN ACCORDANCE WITH APPLICABLE REGULATIONS.

LARGE SPILL: DESTROY BY LIQUID INCINERATION. CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

DO NOT STORE OR USE IN HIGH TEMPERATURE AREAS OR NEAR HEAT, SPARKS, OR OPEN FLAME. KEEP CLOSURE TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE. STORE ONLY IN WELL VENTILATED AREAS. AVOID CONTACT WITH OR BREATHING OF VAPORS RELEASED DURING CURING PROCESS.

**OTHER PRECAUTIONS**

DO NOT TAKE INTERNALLY. AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING OF VAPORS OR SPRAY MIST. ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

=====  
**SECTION VIII - CONTROL MEASURES**  
=====**RESPIRATORY PROTECTION**

IF TLV OF THE PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS(SEE SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

**VENTILATION**

PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV (S).

**PROTECTIVE GLOVES**

WEAR RESISTANT GLOVES SUCH AS NITRILE RUBBER.

**EYE PROTECTION**

CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED. CHECK TO SEE IF OTHERS ARE PERMITTED.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

**WORK/HYGIENIC PRACTICES**

WASH HANDS BEFORE EATING, SMOKING, OR USING WASHROOM. SMOKE IN SMOKING PERMITTED AREAS ONLY.

=====  
**SECTION IX - TRANSPORTATION DATA**  
=====

PAINT, NON-REGULATED IF SHIPPED IN CONTAINERS LESS THAN 5 LITERS.

IF SHIPPED IN LARGER CONTAINERS: UN-1263, PAINT 3, PG II  
FLAMMABLE LIQUID

=====  
**SECTION X - DISCLAIMER**  
=====

THE DATA CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION. INDMAR MAKES NO WARRANTY CONCERNING THEIR ACCURACY AND WILL NOT BE LIABLE FOR CLAIMS RELATING TO USE OR RELIANCE ON DATA OR RECOMMENDATIONS CONTAINED HEREIN, REGARDLESS OF WHETHER IT IS CLAIMED THAT THE INFORMATION IS INACCURATE, INCOMPLETE OR OTHERWISE MISLEADING.